PRESTIGE 140 DOWNLIGHT

HIGH OUTPUT ADJUSTABLE DOWNLIGHT

EFFICIENT LIGHTING SYSTEMS

- Die cast aluminium body
- L90B10 at 80,000hours
- CRI 85+
- 3000K & 4000K
- 15°, 24°, 36° and 60° beam options
- Multi directional, pivots on 2 axis with 25° tilt
- Available in black, white or silver finish

PRESTIGE 140 – VERY NARROW

Non Dimmable	DALI Dimmable	CCT	Beam	Lumens	Watts
PR140.02.15.3000.61	PR140.02.15.3000.66	3000K	15°	2380	20
PR140.02.15.4000.61	PR140.02.15.4000.66	4000K	15°	2380	20

PRESTIGE 140 – NARROW

Non Dimmable	DALI Dimmable	CCT	Beam	Lumens	Watts
PR140.02.24.3000.61	PR140.02.24.3000.66	3000K	24°	2290	20
PR140.02.24.4000.61	PR140.02.24.4000.66	4000K	24°	2290	20

PRESTIGE 140 – MEDIUM

Non Dimmable	DALI Dimmable	CCT	Beam	Lumens	Watts
PR140.02.36.3000.61	PR140.02.36.3000.66	3000K	36°	2290	20
PR140.02.36.4000.61	PR140.02.36.4000.66	4000K	36°	2290	20

PRESTIGE 140 – WIDE

Non Dimmable	DALI Dimmable	CCT	Beam	Lumens	Watts
PR140.02.60.3000.61	PR140.02.60.3000.66	3000K	60°	2290	20
PR140.02.60.4000.61	PR140.02.60.4000.66	4000K	60°	2290	20

DIMENSIONS





COLOUR FINISH

white – WH

silver – SIL

black – BLK

Street Address:
39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:
PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522
www.elslighting.com.au