

SK45 UD



Direct Illumination	80°	80°	80°	80°
Delivered Lumens per 1145mm	1735	2067	1660	2085
System Watts per 1145mm	13.5	16.2	21	26
CRI	80+	80+	90+	90+
LED's divisible by	280mm - 7 cells	280mm - 7 cells	280mm - 7 cells	280mm - 7 cells

Indirect Illumination				
Delivered Lumens per 1145mm	512	524		
System Watts per 1145mm	6.5	9		
CRI	80+	90+		
LED's divisible by	100mm	50mm		

General Specifications

Materials - Extruded aluminium body

Optics - Black reflector down with lens technology | opal diffuser up

Warranty - 5 years

Mounting - Surface mounted | Suspended

Accessories - End caps | joiners | coverplate | suspension | mitered corners - with coverplate

Luminaire Length - Custom lengths made to order divisible as per above

LED Specifications

Colour Temperature - 3000K | 4000K

Colour Deviation - 3 x SDCM

Lifetime - 80+ - L80B10 75,000hours

- 90+ - L80B10 50,000hours

- 80+ - L80B10 60,000hours (upward illumination)

Driver Specifications (integral)

Dimming - Non dimmable | DALI dimmable | Casambi


Custom Luminaire Modifications - 2700K | white tunable | 65° optics | screwless endcaps (pictured above)

Finishes

Black



White




Custom Powdercoat





SK45



HOW TO ORDER

SK45UD . 16 . 6 . 93 . 80 . XXXX . 61 . W

profile . wattage per meter down . wattage per meter up . CRI CCT . beam angle . profile length in mm . dimming type . colour finish

Street Address:
39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:
PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522
www.elslighting.com.au

