

# SL30 UD



## Direct Illumination

Delivered Lumens per meter	690	1020	682	1135	1570
System Watts per meter	10.5	15.8	14.5	25	35
CRI	80+	80+	90+	90+	90+
LED's divisible by	100mm	100mm	50mm	50mm	50mm

## Indirect Illumination

Delivered Lumens per meter	400	430
System Watts per meter	5	8
CRI	80+	90+
LED's divisible by	100mm	50mm



## General Specifications

Materials - Extruded aluminium body | polycarbonate diffuser

Optics - opal flat diffuser | opal U diffuser

Warranty - 5 years

Mounting - Surface mounted | Trimless Recessed | Suspended

Accessories - End caps | joiners | suspension | mitered corners

Luminaire Length - Custom lengths made to order divisible as per above

## LED Specifications

Colour Temperature - 3000K | 4000K

Colour Deviation - 3 x SDCM

Lifetime - 80+ - L80B10 50,000hours

- 90+ - L80B10 60,000hours

## Driver Specifications

Dimming - Non dimmable | DALI dimmable | Casambi

Custom Luminaire Modifications - 2700K | RGBW | white tunable | IP54 |


screwless endcaps (pictured above)

## Finishes

Black



White





Custom Powdercoat





SL30 UD  
flat diffuser

SL30 UD  
U diffuser



## HOW TO ORDER

SL30UD	.	35	.	5	.	93	.	F	.	XXXX	.	61	.	W
profile		wattage per meter down		wattage per meter up		CRI CCT		lens type		profile length in mm		dimming type		colour finish

**Street Address:**  
39 Tinning Street, Brunswick,  
Victoria, 3056, Australia

**Postal Address:**  
PO BOX 5084  
Moreland West VIC 3055

T +61 3 9222 5522  
[www.elslighting.com.au](http://www.elslighting.com.au)

