ARCHI 10

Project name:

Type number: Quantity: Date:



Product Details

Absolute luminous flux (lm)	550 - 694 lm
Power (W)	9W
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K
Colour deviation	3 SDCM
Dimming methods	Non Dim / DALI / Bluetooth (Casambi)
Lumen maintenance (hours)	L70 > 70,000 hours
Driver	Remote
Input voltage	24V
Housing material	Silicone
IP rating	IP67
Warranty	5 years

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Configurator

How to specify

Select from the available options to configure luminaire

AR10.____.____.____.____.____.____

Type

HB	Horizontal Bend
VB	Vertical Bend

Height & Length

1000	1000 mm

Output

9	9W 550lm - 694lm

CRI CCT

927	90+ 2700K
93	90+ 3000K
935	90+ 3500K
94	90+ 4000K

Dimming

61	Non Dim
66	DALI
68	Bluetooth (Casambi)

Options

1B	1 Bottom Cable Entry
1D	1 Direct End Cable Entry
1L	1 Left Cable Entry
1R	1 Right Cable Entry

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Accessories

AR10 Fixed Mounting Channel
AR10.FIXED CHANNEL

AR10 Flexible Mounting Channel
AR10.FLEXIBLE CHANNEL

AR10 Individual Mounting Clips
AR10.INDIVIDUAL CLIPS

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.