DATASHEET AR15

ARCHI 15

Project name:

Type number: Quantity: Date:



Product Details

Absolute luminous flux (lm)	1209 - 1432 lm
Power (W)	12W
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K
Colour deviation	3 SDCM
Dimming methods	Non Dim / DALI
Lumen maintenance (hours)	L70 > 70,000 hours
Driver	Remote
Input voltage	24V
Housing material	Silicone
IP rating	IP67
Warranty	5 years

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Configurator

How to specify

Select from the available options to configure luminaire

AR15.____.____.____.____.____.____

Type	Height & Length	Output	CRI CCT	Dimming
VB Vertical Bend	1000 1000 mm	12 12W 1209lm - 1432lm	927 90+ 2700K	61 Non Dim
			93 90+ 3000K	66 DALI
			935 90+ 3500K	
			94 90+ 4000K	

Options

1B 1 Bottom Cable Entry
1D 1 Direct End Cable Entry
1L 1 Left Cable Entry
1R 1 Right Cable Entry

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.