DATASHEET AR27

ARCHI 27

Project name:

Type number: Quantity: Date:



Product Details

Absolute luminous flux (lm)	1560 - 1970 lm
Power (W)	24W
Optic options	20° x 55° / 25°
CRI	90+
CCT	2700K / 3000K / 4000K
Colour deviation	3 SDCM
Dimming methods	Non Dim / DALI
Lumen maintenance (hours)	L70 > 70,000 hours
Driver	Remote
Input voltage	24V
Housing material	Silicone
Optic material	Silicone
IP rating	IP67
Warranty	5 years

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Configurator

How to specify

Select from the available options to configure luminaire

AR27.____.____.____.____.____.____.____

Type	Height & Length	Output	Optic	CRI CCT
3D 3D BEND	1000 1000 mm	24 24W 1560lm - 1970lm	20x55 20° x 55°	927 90+ 2700K
			25 25°	93 90+ 3000K
				94 90+ 4000K

Dimming	Options
61 Non Dim	1B 1 Bottom Cable Entry
66 DALI	1D 1 Direct End Cable Entry

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.