DATASHEET FFL150

FLEX 150

Project name:

Type number: Quantity: Date:



Product Details

Absolute luminous flux (lm)	1015 - 4008 lm
Power (W)	10 - 36W
Optic options	66° / 80° / Oval
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K
Colour deviation	3 SDCM
Dimming methods	Non Dim / DALI / Bluetooth (Casambi)
Lumen maintenance (hours)	L90B10 > 90,000 hours
Driver	Remote
Input voltage	240v
Housing material	Aluminium
Optic material	PMMA Clear Lens
Warranty	7 years
Country of origin	Australia
Cut out size	Ø150 mm
Weight	1.6 kg

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Configurator

How to specify

Select from the available options to configure luminaire

FFL150.____.____.____.____.____

Output

250	10W 1015lm - 1172lm
350	14W 1394lm - 1613lm
500	20W 1919lm - 2262lm
700	26W 2589lm - 3041lm
950	36W 3539lm - 4008lm

Optic

66	66°
80	80°
OV	Oval

CRI CCT

927	90+ 2700K
93	90+ 3000K
935	90+ 3500K
94	90+ 4000K

Dimming

61	Non Dim
66	DALI
68	Bluetooth (Casambi)

Housing colour

W	White
B	Black
X	Custom

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Colour Options

Housing colour



Black
B

White
W

Custom
X

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.