DATASHEET FTL35

FLEX 35 Trackspot

Project name:

Type number: Quantity: Date:



Product Details

Absolute luminous flux (lm)	470 - 800 lm
Power (W)	7 - 9W
Optic options	19° / 24° / 25° / 33° / 47° / 51°
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K
Colour deviation	3 SDCM
Dimming methods	Non Dim / DALI / Bluetooth (Casambi)
Lumen maintenance (hours)	L90B10 > 90,000 hours
Driver	Integral
Input voltage	240v
Housing material	Aluminium
Optic material	PMMA Clear Lens
Warranty	7 years
Country of origin	Australia

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Configurator

How to specify

Select from the available options to configure luminaire

FTL35.____.____.____.____.____

Output	Optic*	CRI CCT*	Dimming	Housing colour
150 7W 470lm - 618lm	19 19°	927 90+ 2700K	61 Non Dim	W White
200 9W 605lm - 800lm	24 24°	93 90+ 3000K	66 DALI	B Black
	25 25°	935 90+ 3500K	68 Bluetooth (Casambi)	X Custom
	33 33°	94 90+ 4000K		
	47 47°			
	51 51°			

Notes *

19°, 24°, 33°, 51° (Optic) can only be selected with 90+ 3000K, 90+ 4000K (CRI CCT)
25°, 33°, 47° (Optic) can only be selected with 90+ 2700K, 90+ 3500K (CRI CCT)

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Colour Options

Housing colour



Black
B

White
W

Custom
X

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.