DATASHEET FTL70M

FLEX 70 Mini Track Downlight

Project name:

Type number: Quantity: Date:



Product Details

Absolute luminous flux (lm)	770 - 1615 lm
Power (W)	8 - 14W
Optic options	25° / 34° / 54° / 80° / Linear / Oval
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K
Colour deviation	3 SDCM
Dimming methods	Non Dim / DALI / Bluetooth (Casambi)
Lumen maintenance (hours)	L90B10 > 90,000 hours
Driver	Integral
Input voltage	240v
Housing material	Aluminium
Optic material	PMMA Clear Lens
Warranty	7 years
Country of origin	Australia

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Configurator

How to specify

Select from the available options to configure luminaire

FTL70M.____.____.____.____.____

Output

200	8W 770lm - 945lm
250	10W 955lm - 1172lm
300	12W 1137lm - 1395lm
350	14W 1317lm - 1615lm

Optic

25	25°
34	34°
54	54°
80	80°
LN	Linear*
OV	Oval*

CRI CCT

927	90+ 2700K
93	90+ 3000K
935	90+ 3500K
94	90+ 4000K

Dimming

61	Non Dim
66	DALI
68	Bluetooth (Casambi)

Housing colour

W	White
B	Black
X	Custom

Notes *

Oval (Optic) cannot be selected with Specialty Colour Filter, Halo ring, Honeycomb Louvre, XL Baffle (Accessory)
Linear (Optic) cannot be selected with Specialty Colour Filter, Halo ring, Honeycomb Louvre, XL Baffle (Accessory)

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.

Accessories

Specialty Colour Filter
FTL70M.COLOUR.XXX

High quality borosilicate glass filters for premium colourfast performance. Available in a selection of colours. Easily installed by placing behind the luminaire baffle.



Halo ring
FTL70M.HALO RING

A discreet glowing ring attachment that emits a soft glowing light. Supplied in place of the standard baffle. Easily retrofitted by removing the existing baffle.

Mono.BLK / Mono.WH
FTL70M.MONOPOINT

Honeycomb Louvre
FTL70M.HONEYCOMB

Used to provide additional glare control in sensitive areas. Easily installed by placing behind the luminaire baffle.

XL Baffle
FTL70M.XLB

A deep 17mm baffle to provide extra visual comfort in sensititve areas. Supplied in black as standard. Supplied in place of the standard baffle. Easily retrofitted by removing the existing baffle.

Colour Options

Housing colour

White
W

Black
B

Custom
X

We reserve the right to make technical and design changes. All photometric, spectrometric and electrical data have a tolerance of ±10%.