

ADL125 DOWNLIGHT

BLUETOOTH CONTROLLABLE LED DOWNLIGHT



- Xicato XIM Gen4 technology
- Bluetooth enabled
- Standard CRI 83+ or Artist high CRI 98
- 3000K, 4000K or 2700K upon request
- High quality, mirror finish low glare reflector
- Excellent colour consistency from luminaire to luminaire
- 5 year colour consistency warranty - no colour shift
- Thin 2.5mm white polycarbonate trim
- Made in Australia
- L70B0 at 55,000 hours
- Supplied with 48v remote power supply

XIM GEN4 BLE 48V – 83+ CRI - LOW OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL125.XBL48.W.83.66	ADL125.XBL48.W.83.67	55°	3000K	1300	15.5
ADL125.XBL48.W.84.66	ADL125.XBL48.W.84.67	55°	4000K	1300	15.5

XIM GEN4 BLE 48V – 83+ CRI - HIGH OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL125.XB48.W.83.66	ADL125.XB48.W.83.67	55°	3000K	1861	22
ADL125.XB48.W.84.66	ADL125.XB48.W.84.67	55°	4000K	1861	22




XIM GEN4 BLE 48V – 98 CRI - LOW OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL125.XBL48.W.93.66	ADL125.XBL48.W.93.67	55°	3000K	1300	20
ADL125.XBL48.W.94.66	ADL125.XBL48.W.94.67	55°	4000K	1300	20

XIM GEN4 BLE 48V – 98 CRI - HIGH OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL125.XB48.W.93.66	ADL125.XB48.W.93.67	55°	3000K	1861	28.5
ADL125.XB48.W.94.66	ADL125.XB48.W.94.67	55°	4000K	1861	28.5

COLOUR FINISH

-  white - WH
-  silver - SIL
-  black - BLK

OPTIONAL ACCESSORIES

Frosted glass inlay IP44** -
Order code - SDL125-G4




Clear glass inlay IP44** -
Order code - SDL125-G5



**IP Rating is from below the ceiling only

DIMENSIONS



Street Address:
39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:
PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522
www.elslighting.com.au

