

ADL66 DOWNLIGHT

BLUETOOTH CONTROLLABLE LED DOWNLIGHT



- Xicato XIM Gen4 technology
- Bluetooth enabled
- Standard CRI 83+ or Artist high CRI 98
- 3000K, 4000K or 2700K upon request
- High quality, mirror finish low glare reflector
- Excellent colour consistency from luminaire to luminaire
- 5 year colour consistency warranty - no colour shift
- Thin 1.3mm white polycarbonate trim
- Made in Australia
- L70B0 at 55,000 hours
- Supplied with 48v remote power supply

XIM GEN4 BLE 48V – 83+ CRI - LOW OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL66.XBL48.N.83.66	ADL66.XBL48.N.83.67	28°	3000K	690	8.5
ADL66.XBL48.N.84.66	ADL66.XBL48.N.84.67	28°	4000K	690	8.5
ADL66.XBL48.M.83.66	ADL66.XBL48.M.83.67	36°	3000K	685	8.5
ADL66.XBL48.M.84.66	ADL66.XBL48.M.84.67	36°	4000K	685	8.5
ADL66.XBL48.W.83.66	ADL66.XBL48.W.83.67	55°	3000K	663	8.5
ADL66.XBL48.W.84.66	ADL66.XBL48.W.84.67	55°	4000K	663	8.5

XIM GEN4 BLE 48V – 98 CRI - HIGH OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL66.XB48.N.83.66	ADL66.XB48.N.83.67	28°	3000K	1150	14
ADL66.XB48.N.84.66	ADL66.XB48.N.84.67	28°	4000K	1150	14
ADL66.XB48.M.83.66	ADL66.XB48.M.83.67	36°	3000K	1142	14
ADL66.XB48.M.84.66	ADL66.XB48.M.84.67	36°	4000K	1142	14
ADL66.XB48.W.83.66	ADL66.XB48.W.83.67	55°	3000K	1105	14
ADL66.XB48.W.84.66	ADL66.XB48.W.84.67	55°	4000K	1105	14

XIM GEN4 BLE 48V – 98 CRI - LOW OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL66.XBL48.N.93.66	ADL66.XBL48.N.93.67	28°	3000K	678	12
ADL66.XBL48.N.94.66	ADL66.XBL48.N.94.67	28°	4000K	678	12
ADL66.XBL48.M.93.66	ADL66.XBL48.M.93.67	36°	3000K	680	12
ADL66.XBL48.M.94.66	ADL66.XBL48.M.94.67	36°	4000K	680	12
ADL66.XBL48.W.93.66	ADL66.XBL48.W.93.67	55°	3000K	670	12
ADL66.XBL48.W.94.66	ADL66.XBL48.W.94.67	55°	4000K	670	12


XIM GEN4 BLE 48V – 98 CRI - HIGH OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL66.XB48.N.93.66	ADL66.XB48.N.93.67	28°	3000K	1130	16
ADL66.XB48.N.94.66	ADL66.XB48.N.94.67	28°	4000K	1130	16
ADL66.XB48.M.93.66	ADL66.XB48.M.93.67	36°	3000K	905	16
ADL66.XB48.M.94.66	ADL66.XB48.M.94.67	36°	4000K	905	16
ADL66.XB48.W.93.66	ADL66.XB48.W.93.67	55°	3000K	895	16
ADL66.XB48.W.94.66	ADL66.XB48.W.94.67	55°	4000K	895	16

COLOUR FINISH




PHOTOMETRICS



ADL66.XB48.M.83.66

DIMENSIONS



Street Address:
39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:
PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522
www.elslighting.com.au

