



- IP65
- Aluminum housing and extruded aluminium column with high corrosion resistance
- Stainless steel fasteners in grade 316
- Durable silicone rubber gasket
- Highly efficient PMMA lens

- Powder coating with high corrosion resistance and chemical chromatised protection
- Optional DALI dimmable
- 48v power supply not included order separately

ORDERING GUIDE



PRAGUE

Model name	Model number	Lumens		Bear M '		EW	T2	Т3	Т4	ME		Temp W40	Weight
PRAGUE 1	LIG-PRA-10001-	795	7.6	30° 5	6° 99°	°x102°	129°x49°	112°x80°	89°x60°	122°x50°	3000K/	4000K	3kg
PRAGUE 2	LIG-PRA-10011-	1660	13.9	30° 5	56° 110	°x103°	139°x55°	123°x85°	105°x69°	139°x60°	3000K/	4000K	5.7kg
PRAGUE 3	LIG-PRA-10021-	2422	19.7	30° 5	56° 109	9°x102°	137°x58	124°x86°	108°x66°	140°x62°	3000K/	4000K	7.0kg



ACCESSORIES



GVK_KGEL
IP68 GEL CONNECTOR

COLOUR GUIDE



02 DARK GREY RAL7043


03 WHITE RAL9003





PRAGUE 1






POWER SUPPLY & VOLTAGE DROP GUIDE

Power	maximum	maximum cable length						
supply	number of luminaires	1.0mm	1.5mm	2.5mm	4.0mm			
75W	8	34M	51M	85M	130M			
150W	16	16M	24M	40M	64M			
240W	26	10M	15M	25M	40M			
320W	35	7M	10M	17M	28M			

This table is a guide only. Power supply not included and must be ordered separately based on individual job requirements.

PRAGUE 2






POWER SUPPLY & VOLTAGE DROP GUIDE

Power	maximum	maximum cable length						
supply	number of luminaires	1.0mm	1.5mm	2.5mm	4.0mm			
75W	4	70M	100M	170M	260M			
150W	9	30M	45M	75M	120M			
240W	15	18M	27M	45M	72M			
320W	20	14M	21M	35M	56M			

This table is a guide only. Power supply not included and must be ordered separately based on individual job requirements.

PRAGUE 3





POWER SUPPLY & VOLTAGE DROP GUIDE

Power		maximum cable length						
supply	number of luminaires	1.0mm	1.5mm	2.5mm	4.0mm			
75W	3	90M	135M	220M	350M			
150W	6	45M	67M	110M	170M			
240W	11	25M	37M	62M	100M			
320W	14	20M	30M	50M	80M			

This table is a guide only. Power supply not included and must be ordered separately based on individual job requirements.



