

SML330 CEILING LIGHT

DIFFUSED LED CEILING LIGHT



- 2 outputs available
- 3000K or 4000K
- CRI >80
- Die cast aluminium base powdercoated
- Injection moulded polycarbonate lens
- Available in white, black or silver base (custom colours available upon request)
- Made in Australia
- IPX4 version available

SML330 LED

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	CCT	Lumens	Watts
SML330.24.3000.61	SML330.24.3000.63	SML330.24.3000.66	3000K	1682	22
SML330.24.4000.61	SML330.24.4000.63	SML330.24.4000.66	4000K	1682	20
SML330.35.3000.61	SML330.35.3000.63	SML330.35.3000.66	3000K	2319	30
SML330.35.4000.61	SML330.35.4000.63	SML330.35.4000.66	4000K	2319	27


IPX4 VERSION

To specify the product as IPX4 add .IP to the end of the part code

COLOUR FINISH

 white - WH


 silver - SIL

 black - BLK




custom powdercoat colour

PHOTOMETRICS





SML330.24.3000.61



SML330.35.3000.61

DIMENSIONS



Street Address:

39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:

PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522

www.elslighting.com.au

