

# ADL125 DOWNLIGHT

## LED RECESSED DOWNLIGHT



- Xicato XTM technology
- Standard CRI 83+ or Artist high CRI 98
- 3000K, 4000K or 2700K upon request
- High quality, mirror finish low glare reflector
- Excellent colour consistency from luminaire to luminaire
- 5 year colour consistency warranty - no colour shift
- Thin 2.5mm white polycarbonate trim
- Made in Australia
- L70B0 at 55,000 hours

### XTM 240V – 83+ CRI

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Beam	CCT	Lumens	Watts
ADL125.XTM5W.8030.61	ADL125.XTM5W.8030.63	ADL125.XTM5W.8030.66	55°	3000K	1422	13.5
ADL125.XTM5W.8040.61	ADL125.XTM5W.8040.63	ADL125.XTM5W.8040.66	55°	4000K	1422	13.5
ADL125.XTM7W.8030.61	ADL125.XTM7W.8030.63	ADL125.XTM7W.8030.66	55°	3000K	2034	19
ADL125.XTM7W.8040.61	ADL125.XTM7W.8040.63	ADL125.XTM7W.8040.66	55°	4000K	2034	19

### XTM 240V – 98 CRI

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Beam	CCT	Lumens	Watts
ADL125.XTM5W.9530.61	ADL125.XTM5W.9530.63	ADL125.XTM5W.9530.66	55°	3000K	1168	11.5
ADL125.XTM5W.9540.61	ADL125.XTM5W.9540.63	ADL125.XTM5W.9540.66	55°	4000K	1168	11.5
ADL125.XTM7W.9530.61	ADL125.XTM7W.9530.63	ADL125.XTM7W.9530.66	55°	3000K	1386	16.5
ADL125.XTM7W.9540.61	ADL125.XTM7W.9540.63	ADL125.XTM7W.9540.66	55°	4000K	1386	16.5

### COLOUR FINISH



### OPTIONAL ACCESSORIES

Frosted glass inlay IP44\*\* -  
Order code - SDL125-G4



Clear glass inlay IP44\*\* -  
Order code - SDL125-G5




Vandal resistant lens -  
Order code - SDL125-VR



\*\*IP Rating is from below the ceiling only

### DIMENSIONS – XTM



**Street Address:**  
39 Tinning Street, Brunswick,  
Victoria, 3056, Australia

**Postal Address:**  
PO BOX 5084  
Moreland West VIC 3055

T +61 3 9222 5522  
www.elslighting.com.au

