

ADL90 DOWNLIGHT

BLUETOOTH CONTROLLABLE LED DOWNLIGHT



- Xicato XIM Gen4 technology
- Bluetooth enabled
- Standard CRI 83+ or Artist high CRI 98
- 3000K, 4000K or 2700K upon request
- High quality, mirror finish low glare reflector
- Excellent colour consistency from luminaire to luminaire
- 5 year colour consistency warranty - no colour shift
- Thin 2.5mm white polycarbonate trim
- Made in Australia
- L70B0 at 55,000 hours
- Supplied with 48v remote power supply

XIM GEN4 BLE 48V – 83+ CRI LOW OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL90.XBL48.N.83.66	ADL90.XBL48.N.83.67	21°	3000K	778	9
ADL90.XBL48.N.84.66	ADL90.XBL48.N.84.67	21°	4000K	778	9
ADL90.XBL48.M.83.66	ADL90.XBL48.M.83.67	35°	3000K	739	9
ADL90.XBL48.M.84.66	ADL90.XBL48.M.84.67	35°	4000K	739	9
ADL90.XBL48.W.83.66	ADL90.XBL48.W.83.67	55°	3000K	692	9
ADL90.XBL48.W.84.66	ADL90.XBL48.W.84.67	55°	4000K	692	9

XIM GEN4 BLE 48V – 83+ CRI HIGH OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL90.XB48.N.83.66	ADL90.XB48.N.83.67	21°	3000K	1198	14.5
ADL90.XB48.N.84.66	ADL90.XB48.N.84.67	21°	4000K	1198	14.5
ADL90.XB48.M.83.66	ADL90.XB48.M.83.67	35°	3000K	1137	14.5
ADL90.XB48.M.84.66	ADL90.XB48.M.84.67	35°	4000K	1137	14.5
ADL90.XB48.W.83.66	ADL90.XB48.W.83.67	55°	3000K	1165	14.5
ADL90.XB48.W.84.66	ADL90.XB48.W.84.67	55°	4000K	1165	14.5

XIM GEN4 BLE 48V – 98 CRI LOW OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL90.XBL48.N.93.66	ADL90.XBL48.N.93.67	21°	3000K	777	12
ADL90.XBL48.N.94.66	ADL90.XBL48.N.94.67	21°	4000K	777	12
ADL90.XBL48.M.93.66	ADL90.XBL48.M.93.67	35°	3000K	734	12
ADL90.XBL48.M.94.66	ADL90.XBL48.M.94.67	35°	4000K	734	12
ADL90.XBL48.W.93.66	ADL90.XBL48.W.93.67	55°	3000K	718	12
ADL90.XBL48.W.94.66	ADL90.XBL48.W.94.67	55°	4000K	718	12

XIM GEN4 BLE 48V – 98 CRI HIGH OUTPUT

DALI Dimmable	Bluetooth Dimmable	Beam	CCT	Lumens	Watts
ADL90.XB48.N.93.66	ADL90.XB48.N.93.67	21°	3000K	1196	20
ADL90.XB48.N.94.66	ADL90.XB48.N.94.67	21°	4000K	1196	20
ADL90.XB48.M.93.66	ADL90.XB48.M.93.67	35°	3000K	1130	20
ADL90.XB48.M.94.66	ADL90.XB48.M.94.67	35°	4000K	1130	20
ADL90.XB48.W.93.66	ADL90.XB48.W.93.67	55°	3000K	1105	20
ADL90.XB48.W.94.66	ADL90.XB48.W.94.67	55°	4000K	1105	20


ACCESSORIES - IPX4

To specify the downlight as IPX4 add "IP" to the end of the part code
IPX4 rating is from below the ceiling only and uses a clear lens

COLOUR FINISH




PHOTOMETRICS



ADL90.XB48.N.83.66

DIMENSIONS



Street Address:
39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:
PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522
www.elslighting.com.au

