

ADL66 DOWNLIGHT

LED RECESSED DOWNLIGHT



- Xicato XTM technology
- Standard CRI 83+ or Artist high CRI 98
- 3000K, 4000K or 2700K upon request
- High quality, mirror finish low glare reflector
- Excellent colour consistency from luminaire to luminaire
- 5 year colour consistency warranty - no colour shift
- Thin 1.3mm white polycarbonate trim
- Made in Australia
- L70B0 at 55,000 hours
- UGR<19
- Available in a Bluetooth dimmable version refer to Smart Lighting Catalogue

NIGHTLIGHT XTM 240V – 83+ CRI

Non Dimmable	CCT	Lumens	Watts
ADL66.XTM2.8030.61	3000K	250	3
ADL66.XTM2.8040.61	4000K	250	3

XTM 240V – 83+ CRI

Non Dimmable	DALI Dimmable	Beam	CCT	Lumens	Watts
ADL66.XTM7N.8030.61	ADL66.XTM7N.8030.66	24°	3000K	607	6
ADL66.XTM7N.8040.61	ADL66.XTM7N.8040.66	24°	4000K	607	6
ADL66.XTM3M.8030.61	ADL66.XTM3M.8030.66	35°	3000K	626	6
ADL66.XTM3M.8040.61	ADL66.XTM3M.8040.66	35°	4000K	626	6
ADL66.XTM3W.8030.61	ADL66.XTM3W.8030.66	55°	3000K	607	6
ADL66.XTM3W.8040.61	ADL66.XTM3W.8040.66	55°	4000K	607	6


XTM 240V – 98 CRI

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Beam	CCT	Lumens	Watts
ADL66.XTM7N.9530.61	ADL66.XTM7N.9530.63	ADL66.XTM7N.9530.66	24°	3000K	621	8
ADL66.XTM7N.9540.61	ADL66.XTM7N.9540.63	ADL66.XTM7N.9540.66	24°	4000K	621	8
ADL66.XTM3M.9530.61	ADL66.XTM3M.9530.63	ADL66.XTM3M.9530.66	35°	3000K	645	8
ADL66.XTM3M.9540.61	ADL66.XTM3M.9540.63	ADL66.XTM3M.9540.66	35°	4000K	645	8
ADL66.XTM3W.9530.61	ADL66.XTM3W.9530.63	ADL66.XTM3W.9530.66	55°	3000K	621	8
ADL66.XTM3W.9540.61	ADL66.XTM3W.9540.63	ADL66.XTM3W.9540.66	55°	4000K	621	8


COLOUR FINISH



PHOTOMETRICS




ADL66.XTM3W.8030.61




ADL66.XTM7N.8030.61

DIMENSIONS – 24° & NIGHTLIGHT



DIMENSIONS – 35° & 55°



Street Address:
39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:
PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522
www.elslighting.com.au

