

ADL110 PENDANT

LED PENDANT



- Xicato XTM technology
- Standard CRI 83+ or Artist high CRI 98
- 3000K or 4000K
- Aluminium body, powdercoated
- High quality, mirror finish low glare reflector
- Excellent colour consistency from luminaire to luminaire
- 5 year colour consistency warranty - no colour shift
- Made in Australia
- 1mtr standard drop
- L70B0 at 55,000 hours
- Available in a Bluetooth dimmable version refer to Smart Lighting Catalogue

XTM 240V – 83+ CRI – LOW OUTPUT

| Non Dimmable | Trailing Edge Dimmable | DALI Dimmable | Beam | CCT | Lumens | Watts |
|-----------------------|------------------------|-----------------------|------|-------|--------|-------|
| ADL110.XTM5M.8030.61P | ADL110.XTM5M.8030.63P | ADL110.XTM5M.8030.66P | 31° | 3000K | 1385 | 13.5 |
| ADL110.XTM5M.8040.61P | ADL110.XTM5M.8040.63P | ADL110.XTM5M.8040.66P | 31° | 4000K | 1385 | 13.5 |
| ADL110.XTM5W.8030.61P | ADL110.XTM5W.8030.63P | ADL110.XTM5W.8030.66P | 55° | 3000K | 1267 | 13.5 |
| ADL110.XTM5W.8040.61P | ADL110.XTM5W.8040.63P | ADL110.XTM5W.8040.66P | 55° | 4000K | 1267 | 13.5 |

XTM 240V – 83+ CRI – HIGH OUTPUT

| Non Dimmable | Trailing Edge Dimmable | DALI Dimmable | Beam | CCT | Lumens | Watts |
|-----------------------|------------------------|-----------------------|------|-------|--------|-------|
| ADL110.XTM7M.8030.61P | ADL110.XTM7M.8030.63P | ADL110.XTM7M.8030.66P | 31° | 3000K | 1861 | 18.5 |
| ADL110.XTM7M.8040.61P | ADL110.XTM7M.8040.63P | ADL110.XTM7M.8040.66P | 31° | 4000K | 1861 | 18.5 |
| ADL110.XTM7W.8030.61P | ADL110.XTM7W.8030.63P | ADL110.XTM7W.8030.66P | 55° | 3000K | 1708 | 18.5 |
| ADL110.XTM7W.8040.61P | ADL110.XTM7W.8040.63P | ADL110.XTM7W.8040.66P | 55° | 4000K | 1708 | 18.5 |

XTM 240V – 98 CRI – LOW OUTPUT

| Non Dimmable | Trailing Edge Dimmable | DALI Dimmable | Beam | CCT | Lumens | Watts |
|-----------------------|------------------------|-----------------------|------|-------|--------|-------|
| ADL110.XTM5M.9530.61P | ADL110.XTM5M.9530.63P | ADL110.XTM5M.9530.66P | 31° | 3000K | 980 | 11.5 |
| ADL110.XTM5M.9540.61P | ADL110.XTM5M.9540.63P | ADL110.XTM5M.9540.66P | 31° | 4000K | 980 | 11.5 |
| ADL110.XTM5W.9530.61P | ADL110.XTM5W.9530.63P | ADL110.XTM5W.9530.66P | 55° | 3000K | 1105 | 11.5 |
| ADL110.XTM5W.9540.61P | ADL110.XTM5W.9540.63P | ADL110.XTM5W.9540.66P | 55° | 4000K | 1105 | 11.5 |

XTM 240V – 98 CRI – HIGH OUTPUT

| Non Dimmable | Trailing Edge Dimmable | DALI Dimmable | Beam | CCT | Lumens | Watts |
|-----------------------|------------------------|-----------------------|------|-------|--------|-------|
| ADL110.XTM7M.9530.61P | ADL110.XTM7M.9530.63P | ADL110.XTM7M.9530.66P | 31° | 3000K | 1300 | 16.5 |
| ADL110.XTM7M.9540.61P | ADL110.XTM7M.9540.63P | ADL110.XTM7M.9540.66P | 31° | 4000K | 1300 | 16.5 |
| ADL110.XTM7W.9530.61P | ADL110.XTM7W.9530.63P | ADL110.XTM7W.9530.66P | 55° | 3000K | 1312 | 16.5 |
| ADL110.XTM7W.9540.61P | ADL110.XTM7W.9540.63P | ADL110.XTM7W.9540.66P | 55° | 4000K | 1312 | 16.5 |

COLOURED FLEX



pink



white



black



green



blue



red



orange



yellow

COLOUR FINISH



white - WH



silver - SIL




black - BLK




custom powdercoat colour

PHOTOMETRICS




ADL110.XTM7W.8030.61P




ADL110.XTM5W.8030.61P

DIMENSIONS



NON DIMMABLE



DIMMABLE

Street Address:
39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:
PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522
www.elslighting.com.au

