

LUXIENT90 PENDANT

PREMIUM LED PENDANT



- 95+ CRI
- up to 107 Lm/w
- 3000K or 4000K
- High quality, low glare reflectors
- Black baffle for superior glare control
- Made in Australia
- L90B10 up to 90,000 hours
- 2 X SDCM




LUXIENT 90 PENDANT – 250mA

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Beam	CCT	Lumens	Watts	Lm/W
LX90.250.24.93.61.P	LX90.250.24.93.63.P	LX90.250.24.93.66.P	24°	3000K	1049	10	105
LX90.250.24.94.61.P	LX90.250.24.94.63.P	LX90.250.24.94.66.P	24°	4000K	1071	10	107
LX90.250.35.93.61.P	LX90.250.35.93.63.P	LX90.250.35.93.66.P	35°	3000K	1049	10	105
LX90.250.35.94.61.P	LX90.250.35.94.63.P	LX90.250.35.94.66.P	35°	4000K	1071	10	107
LX90.250.50.93.61.P	LX90.250.50.93.63.P	LX90.250.50.93.66.P	50°	3000K	1049	10	105
LX90.250.50.94.61.P	LX90.250.50.94.63.P	LX90.250.50.94.66.P	50°	4000K	1071	10	107
LX90.250.80.93.61.P	LX90.250.80.93.63.P	LX90.250.80.93.66.P	80°	3000K	930	10	93
LX90.250.80.94.61.P	LX90.250.80.94.63.P	LX90.250.80.94.66.P	80°	4000K	951	10	95


LUXIENT 90 PENDANT– 350mA

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Beam	CCT	Lumens	Watts	Lm/W
LX90.350.24.93.61.P	LX90.350.24.93.63.P	LX90.350.24.93.66.P	24°	3000K	1330	14	95
LX90.350.24.94.61.P	LX90.350.24.94.63.P	LX90.350.24.94.66.P	24°	4000K	1356	14	97
LX90.350.35.93.61.P	LX90.350.35.93.63.P	LX90.350.35.93.66.P	35°	3000K	1330	14	95
LX90.350.35.94.61.P	LX90.350.35.94.63.P	LX90.350.35.94.66.P	35°	4000K	1356	14	97
LX90.350.50.93.61.P	LX90.350.50.93.63.P	LX90.350.50.93.66.P	50°	3000K	1330	14	95
LX90.350.50.94.61.P	LX90.350.50.94.63.P	LX90.350.50.94.66.P	50°	4000K	1356	14	97
LX90.350.80.93.61.P	LX90.350.80.93.63.P	LX90.350.80.93.66.P	80°	3000K	1263	14	90
LX90.350.80.94.61.P	LX90.350.80.94.63.P	LX90.350.80.94.66.P	80°	4000K	1288	14	90

LUXIENT 90 PENDANT




NON DIM



DALI DIMMABLE

Body Finishes

Black	
White	
Custom	

Custom Luminaire Modifications

2700K and 3500K colour temperature

80+ CRI

Custom outputs

Casambi dimming

Ceiling Rose Options


Surface Flush Mount (requires recessing into ceiling to achieve flush mount)



*Surface mounted ceiling rose supplied unless otherwise specified

Optional Reflector Finishes

Satin black Champagne Satin gold



Matt white Metalised Brass

*Metalised reflectors supplied unless otherwise specified

Optional Cloth Flex

Black Gold White



3 core or 5 core

Yellow

Orange

Red

Emerald

Light Blue



3 core only

*1mtr clear flex supplied as standard unless otherwise specified



Street Address:

39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:

PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522

www.elslighting.com.au

