

LUXIENT66 SURFACE

PREMIUM LED SURFACE MOUNTED DOWNLIGHT



- 95+ CRI
- up to 101 Lm/w
- 3000K or 4000K
- High quality, low glare reflectors
- Black baffle for superior glare control
- Made in Australia
- L90B10 up to 90,000 hours
- 2 X SDCM




LUXIENT 66 SURFACE– 200mA

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Beam	CCT	Lumens	Watts	Lm/W
LX66.200.24.93.61.S	LX66.200.24.93.63.S	LX66.200.24.93.66.S	24°	3000K	788	8	98
LX66.200.24.94.61.S	LX66.200.24.94.63.S	LX66.200.24.94.66.S	24°	4000K	811	8	101
LX66.200.35.93.61.S	LX66.200.35.93.63.S	LX66.200.35.93.66.S	35°	3000K	788	8	98
LX66.200.35.94.61.S	LX66.200.35.94.63.S	LX66.200.35.94.66.S	35°	4000K	811	8	101
LX66.200.50.93.61.S	LX66.200.50.93.63.S	LX66.200.50.93.66.S	50°	3000K	788	8	98
LX66.200.50.94.61.S	LX66.200.50.94.63.S	LX66.200.50.94.66.S	50°	4000K	811	8	101

LUXIENT 66 SURFACE– 250mA

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Beam	CCT	Lumens	Watts	Lm/W
LX66.250.24.93.61.S	LX66.250.24.93.63.S	LX66.250.24.93.66.S	24°	3000K	985	10	98
LX66.250.24.94.61.S	LX66.250.24.94.63.S	LX66.250.24.94.66.S	24°	4000K	1014	10	101
LX66.250.35.93.61.S	LX66.250.35.93.63.S	LX66.250.35.93.66.S	35°	3000K	985	10	98
LX66.250.35.94.61.S	LX66.250.35.94.63.S	LX66.250.35.94.66.S	35°	4000K	1014	10	101
LX66.250.50.93.61.S	LX66.250.50.93.63.S	LX66.250.50.93.66.S	50°	3000K	985	10	98
LX66.250.50.94.61.S	LX66.250.50.94.63.S	LX66.250.50.94.66.S	50°	4000K	1014	10	101

LUXIENT 66 SURFACE



NON DIM

DIMMING

Body Finishes



Custom Luminaire Modifications

2700K and 3500K colour temperature

80+ CRI

Custom outputs

Casambi dimming

Optional Reflector finishes

Satin black

Champagne

Satin gold



Matt white

Metalised

Brass



Street Address:

39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:

PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522

www.elslighting.com.au

