

LOOP80



Direct Illumination

Delivered Lumens per meter	1374	2157	3020	3790
System Watts per meter	16	33	25	32
CRI	80+	90+	HO 80+	HO 80+
LED's divisible by	100mm	50mm	140mm	140mm

General Specifications

Materials - Extruded aluminium body | polycarbonate diffuser

Optics - Opal

Warranty - 5 years

Mounting - Surface mounted | suspended

Accessories - End caps | joiners | suspension

Luminaire Length - Custom lengths made to order divisible as per above

LED Specifications

Colour Temperature - 3000K | 4000K

Colour Deviation - 3 x SDCM

Lifetime -80+ - L80B10 50,000hours

-HO 80+ - L80B10 72,000hours

-90+ - L80B10 60,000hours

Driver Specifications

Dimming - Non dimmable | DALI dimmable | Casambi-integral


Custom Luminaire Modifications - 2700K | RGBW | white tunable

Finishes

Black




White



Custom Powdercoat




Loop 80 Integral (LPS80)



Integral driver

Loop 80 Remote(LPP80)



remote driver

HOW TO ORDER

LPP80

profile

33

wattage
per meter

93

CRI CCT

XXXX

profile length
in mm

61

dimming
type

W

colour
finish



Street Address:

39 Tinning Street, Brunswick,
Victoria, 3056, Australia

Postal Address:

PO BOX 5084
Moreland West VIC 3055

T +61 3 9222 5522

www.elslighting.com.au

