

NIGHTFALL 414 SURFACE MOUNT

Premium surface mount linear downlight



Product Description

The most magical lights are seen at nightfall. And so it is with the Nightfall 414 Surface Mount Linear Downlight. The magic of this luminaire is that it presents beautifully and performs brilliantly without imposing on the overall design aesthetic.

Available with Variable Output Technology the Nightfall 414 ensures complete lighting control and performance for the user. This amazing luminaire also features a dual optical system that enables both glare control and beam intensity.

Product Details

Absolute luminous flux	1250lm - 2698lm
System watts	12W / 14W / 18W / 22W
Luminaire efficacy	up to 120lm/W
Colour deviation	3 SDCM
Colour rendition Index	>90
Correlated colour temperature	3000K / 4000K / 2700K - 6500K
Lumen maintenance	L80B10 50,000hours
Driver	Integral
Dimming method	Trailing edge / DALI / Casambi
Optic	PMMA Clear Lens & PC Louvre
Louvre finish	Black / White
Beam angle	65° / 80° / Asymmetric
Luminaire housing	Aluminium
Luminaire housing colour	Black / White / Custom
Country of origin	Australia

HOUSING LOUVRE EXAMPLES



BLACK IN WHITE



ALL WHITE



ALL BLACK



WHITE IN BLACK

Product Variants

TECHNICAL SPECIFICATIONS - BLACK LOUVRE

NON DIMMABLE	TRAILING EDGE DIMMABLE	DALI DIMMABLE	CASAMBI DIMMABLE	BEAM ANGLE	CCT	CRI	LUMENS	WATTS
NFS414B.300.65.93.61	NFS414B.300.65.93.63	NFS414B.300.65.93.66	NFS414B.300.65.93.68	65°	3000K	90+	1619	14
NFS414B.300.65.94.61	NFS414B.300.65.94.63	NFS414B.300.65.94.66	NFS414B.300.65.94.68	65°	4000K	90+	1686	14
NFS414B.300.80.93.61	NFS414B.300.80.93.63	NFS414B.300.80.93.66	NFS414B.300.80.93.68	80°	3000K	90+	1542	14
NFS414B.300.80.94.61	NFS414B.300.80.94.63	NFS414B.300.80.94.66	NFS414B.300.80.94.68	80°	4000K	90+	1606	14
NFS414B.400.65.93.61	NFS414B.400.65.93.63	NFS414B.400.65.93.66	NFS414B.400.65.93.68	65°	3000K	90+	2082	18
NFS414B.400.65.94.61	NFS414B.400.65.94.63	NFS414B.400.65.94.66	NFS414B.400.65.94.68	65°	4000K	90+	2176	18
NFS414B.400.80.93.61	NFS414B.400.80.93.63	NFS414B.400.80.93.66	NFS414B.400.80.93.68	80°	3000K	90+	1983	18
NFS414B.400.80.94.61	NFS414B.400.80.94.63	NFS414B.400.80.94.66	NFS414B.400.80.94.68	80°	4000K	90+	2073	18
NFS414B.500.65.93.61	NFS414B.500.65.93.63	NFS414B.500.65.93.66	NFS414B.500.65.93.68	65°	3000K	90+	2581	22
NFS414B.500.65.94.61	NFS414B.500.65.94.63	NFS414B.500.65.94.66	NFS414B.500.65.94.68	65°	4000K	90+	2698	22
NFS414B.500.80.93.61	NFS414B.500.80.93.63	NFS414B.500.80.93.66	NFS414B.500.80.93.68	80°	3000K	90+	2459	22
NFS414B.500.80.94.61	NFS414B.500.80.94.63	NFS414B.500.80.94.66	NFS414B.500.80.94.68	80°	4000K	90+	2570	22

WHITE TUNABLE - BLACK LOUVRE

DALI DIMMABLE	CASAMBI DIMMABLE	BEAM ANGLE	CCT	CRI	LUMENS	WATTS
NFS414B.250.65.WT.66	NFS414B.250.65.WT.68	65°	2700K -6500K	90+	1250-1349	12
NFS414B.250.80.WT.66	NFS414B.250.80.WT.68	80°	2700K -6500K	90+	1191-1285	12
NFS414B.300.65.WT.66	NFS414B.300.65.WT.68	65°	2700K -6500K	90+	1493-1610	14
NFS414B.300.80.WT.66	NFS414B.300.80.WT.68	80°	2700K -6500K	90+	1422-1533	14

Part codes listed are for black cells. For white cells replace 'B' in part code with 'W'.

Product Variants

TECHNICAL SPECIFICATIONS



OTHER LUMINAIRES WITHIN THE FAMILY

NFR100 Recessed
 NFS404 Surface
 NFR404 Recessed
 NFS407 Surface
 NFS407 Surface Asymmetric
 NFR407 Recessed
 NFR407 Recessed Asymmetric
 NFS414 Surface Asymmetric
 NFR414 Recessed
 NFR414 Recessed Asymmetric



Australian made like nothing ELS^e.