IP65 Vandal resistant wall and ceiling luminaire





Product Description

A traditional wall or ceiling mounted bulkhead for exterior applications the Belle offers IP65 protection and vandal resistant in a slim construction.

Manufactured from UV stabalised fire resistant polycabonate the Belle has been designed to stand the test of time and has proven itself in the harsh Australian elements for over 25 years.

Product Details

Absolute luminous flux 1290lm - 1400lm

System watts 16W

Luminaire efficacy up to 87lm/W
Colour deviation 3 SDCM
Colour rendition Index >80

Correlated colour temperature 3000K / 4000K
Lumen maintenance L80B10 60,000hours
Dimming method Non dimm / DALI

Lens UV stabalised opal polycarbonate

Body / Trim UV stabalised flame retardant polycarbonate

Trim colour Black / White / Silver


Country of origin Australia



Product Variants

TECHNICAL SPECIFICATIONS

Non Dimmable	DALI Dimmable	CCT	Lumens	Watts	Trim Colour	
BLW.16.3000.61	BLW.16.3000.66	3000K	1290	16	White	
BLW.16.4000.61	BLW.16.4000.66	4000K	1400	16	White	
BLS.16.3000.61	BLS.16.3000.66	3000K	1290	16	White	
BLS.16.4000.61	BLS.16.4000.66	4000K	1400	16	White	
BLB.16.3000.61	BLB.16.3000.66	3000K	1290	16	White	
BLB.16.4000.61	BLB.16.4000.66	4000K	1400	16L	White	





Australian made like nothing **Els**e.





