

LUXIENT™ 90 DOWNLIGHT | RECESSED

Premium recessed downlight



Product Description

Engineered and built to perform the Luxient 90 recessed downlight offers versatility and endurance in any environment.

The specifically designed reflector system enables the Luxient 90 recessed downlight to deliver exceptional efficacy while still providing superior glare control. Various optics and finishes offer a truly custom approach to achieving the right lighting solution each and every time.

Product Details

Absolute luminous flux	930lm - 1403lm
System watts	10W / 14W
Luminaire efficacy	up to 107lm/W
Colour deviation	2 SDCM
Colour rendition Index	>95
Correlated colour temperature	3000K / 4000K
Lumen maintenance	L90B10 90,000hours
Dimming method	Non dimm / Trailing Edge / DALI / Casambi
Optic	Metallised reflector
Beam angle	24° / 35° / 50° / 80°
Trim	Polycarbonate 2.5mm
Trim colour	Black / White
Country of origin	Australia

CUSTOM LUMINAIRE MODIFICATIONS

2700K and 3500K colour temperature
White tuneable 2700K - 6500K
IPX4 lens

CUSTOM REFLECTOR FINISHES



GOLD

CHAMPAGNE

BRASS

BLACK

WHITE

Product Variants


TECHNICAL SPECIFICATIONS

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Casambi Dimmable	Beam Angle	CCT	Lumens	Watts
LX90.250.24.93.61	LX90.250.24.93.63	LX90.250.24.93.66	LX90.250.24.93.68	24°	3000K	905	10
LX90.250.24.94.61	LX90.250.24.94.63	LX90.250.24.94.66	LX90.250.24.94.68	24°	4000K	982	10
LX90.250.35.93.61	LX90.250.35.93.63	LX90.250.35.93.66	LX90.250.35.93.68	35°	3000K	903	10
LX90.250.35.94.61	LX90.250.35.94.63	LX90.250.35.94.66	LX90.250.35.94.68	35°	4000K	994	10
LX90.250.50.93.61	LX90.250.50.93.63	LX90.250.50.93.66	LX90.250.50.93.68	50°	3000K	1049	10
LX90.250.50.94.61	LX90.250.50.94.63	LX90.250.50.94.66	LX90.250.50.94.68	50°	4000K	1071	10
LX90.250.80.93.61	LX90.250.80.93.63	LX90.250.80.93.66	LX90.250.80.93.68	80°	3000K	930	10
LX90.250.80.94.61	LX90.250.80.94.63	LX90.250.80.94.66	LX90.250.80.94.68	80°	4000K	984	10
LX90.350.24.93.61	LX90.350.24.93.63	LX90.350.24.93.66	LX90.350.24.93.68	24°	3000K	1260	14
LX90.350.24.94.61	LX90.350.24.94.63	LX90.350.24.94.66	LX90.350.24.94.68	24°	4000K	1340	14
LX90.350.35.93.61	LX90.350.35.93.63	LX90.350.35.93.66	LX90.350.35.93.68	35°	3000K	1299	14
LX90.350.35.94.61	LX90.350.35.94.63	LX90.350.35.94.66	LX90.350.35.94.68	35°	4000K	1403	14
LX90.350.50.93.61	LX90.350.50.93.63	LX90.350.50.93.66	LX90.350.50.93.68	50°	3000K	1330	14
LX90.350.50.94.61	LX90.350.50.94.63	LX90.350.50.94.66	LX90.350.50.94.68	50°	4000K	1383	14
LX90.350.80.93.61	LX90.350.80.93.63	LX90.350.80.93.66	LX90.350.80.93.68	80°	3000K	1263	14
LX90.350.80.94.61	LX90.350.80.94.63	LX90.350.80.94.66	LX90.350.80.94.68	80°	4000K	1333	14


Product Variants

TECHNICAL SPECIFICATIONS

LUXIENT 90 - 24° / 35° / 50°



LUXIENT 90 - 80°



OTHER LUMINAIRES WITHIN THE FAMILY

- Luxient 66 - Recessed
- Luxient 66 - Surface mounted
- Luxient 66 - Pendant
- Luxient 66 - Trackspot
- Luxient 90 - Surface mounted
- Luxient 90 - Pendant
- Luxient 90 - Trackspot
- Luxient 110 - Recessed
- Luxient 110 - Surface mounted
- Luxient 110 - Pendant
- Luxient 125 - Recessed
- Luxient 150 - Recessed
- Luxient 150 - Surface mounted
- Luxient 150 - Pendant



Australian made like nothing ELS^e.