

LUXIENT™ 110 DOWNLIGHT | RECESSED

Premium recessed downlight



Product Description

Engineered and built to perform the Luxient 110 recessed downlight offers versatility and endurance in any environment.

The specifically designed reflector system enables the Luxient 110 recessed downlight to deliver exceptional efficacy while still providing superior glare control. Various optics and finishes offer a truly custom approach to achieving the right lighting solution each and every time.

Product Details

Absolute luminous flux	1282lm - 1827lm
System watts	13W / 19W
Luminaire efficacy	up to 100lm/W
Colour deviation	2 SDCM
Colour rendition Index	>95
Correlated colour temperature	3000K / 4000K
Lumen maintenance	L90B10 90,000hours
Dimming method	Non dimm / Trailing Edge / DALI / Casambi
Optic	Metallised reflector
Beam angle	31° / 60° / 85°
Trim	Polycarbonate 2.5mm
Trim colour	Black / White
Country of origin	Australia

CUSTOM LUMINAIRE MODIFICATIONS

2700K and 3500K colour temperature

White tuneable 2700K - 6500K

IPX4 lens

CUSTOM REFLECTOR FINISHES



GOLD



CHAMPAGNE



BRASS



BLACK



WHITE

Product Variants


TECHNICAL SPECIFICATIONS

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Casambi Dimmable	Beam Angle	CCT	Lumens	Watts
LX110.350.31.93.61	LX110.350.31.93.63	LX110.350.31.93.66	LX110.350.31.93.68	31°	3000K	1282	13
LX110.350.31.94.61	LX110.350.31.94.63	LX110.350.31.94.66	LX110.350.31.94.68	31°	4000K	1307	13
LX110.350.60.93.61	LX110.350.60.93.63	LX110.350.60.93.66	LX110.350.60.93.68	60°	3000K	1282	13
LX110.350.60.94.61	LX110.350.60.94.63	LX110.350.60.94.66	LX110.350.60.94.68	60°	4000K	1307	13
LX110.350.85.93.61	LX110.350.85.93.63	LX110.350.85.93.66	LX110.350.85.93.68	85°	3000K	1295	13
LX110.350.85.94.61	LX110.350.85.94.63	LX110.350.85.94.66	LX110.350.85.94.68	85°	4000K	1320	13
LX110.500.31.93.61	LX110.500.31.93.63	LX110.500.31.93.66	LX110.500.31.93.68	31°	3000K	1772	19
LX110.500.31.94.61	LX110.500.31.94.63	LX110.500.31.94.66	LX110.500.31.94.68	31°	4000K	1807	19
LX110.500.60.93.61	LX110.500.60.93.63	LX110.500.60.93.66	LX110.500.60.93.68	60°	3000K	1772	19
LX110.500.60.94.61	LX110.500.60.94.63	LX110.500.60.94.66	LX110.500.60.94.68	60°	4000K	1807	19
LX110.500.85.93.61	LX110.500.85.93.63	LX110.500.85.93.66	LX110.500.85.93.68	85°	3000K	1792	19
LX110.500.85.94.61	LX110.500.85.94.63	LX110.500.85.94.66	LX110.500.85.94.68	85°	4000K	1827	19


Product Variants

TECHNICAL SPECIFICATIONS


LUXIENT 110 - 31°



LUXIENT 110 - 60°



LUXIENT 110 - 85°



OTHER LUMINAIRES WITHIN THE FAMILY

- Luxient 66 - Recessed
- Luxient 66 - Surface mounted
- Luxient 66 - Pendant
- Luxient 66 - Trackspot
- Luxient 90 - Recessed
- Luxient 90 - Surface mounted
- Luxient 90 - Pendant
- Luxient 90 - Trackspot
- Luxient 110 - Surface mounted
- Luxient 110 - Pendant
- Luxient 125 - Recessed
- Luxient 150 - Recessed
- Luxient 150 - Surface mounted
- Luxient 150 - Pendant



Australian made like nothing ELS^e.