

## LUXIENT™ 150 DOWNLIGHT | SURFACE MOUNTED

Premium surface mounted downlight



## Product Description

With an echo to classic designs of the past, but with an eye firmly on the future the Luxient 150 surface mounted downlight offers perfect versatility and performance in any environment. Presenting in a sleek, modern cylindrical housing this luminaire is available in an array of finishes.

The specifically designed reflector system enables the Luxient 150 surface mounted downlight to deliver exceptional luminaire efficacy while still providing superior glare control.

## Product Details

Absolute luminous flux	2477lm - 3909lm
System watts	28W / 38W
Luminaire efficacy	up to 104lm/W
Colour deviation	2 SDCM
Colour rendition Index	>95
Correlated colour temperature	3000K / 4000K
Lumen maintenance	L90B10 90,000hours
Dimming method	Non dimm / Trailing Edge / DALI / Casambi
Optic	Metalised reflector
Beam angle	55° / 85°
Housing	Aluminium
Housing colour	Black / White / Custom
Country of origin	Australia

## CUSTOM LUMINAIRE MODIFICATIONS

2700K and 3500K colour temperature  
 Custom housing height  
 White tuneable 2700K-6500k  
 Remote gear

## CUSTOM REFLECTOR FINISHES




GOLD



CHAMPAGNE



BRASS



BLACK




WHITE

## Product Variants

### TECHNICAL SPECIFICATIONS

Non Dimmable	Trailing Edge Dimmable	DALI Dimmable	Casambi Dimmable	Beam Angle	CCT	Lumens	Watts
LX150.500.55.93.61.S	LX150.500.55.93.63.S	LX150.500.55.93.66.S	LX150.500.55.93.68.S	55°	3000K	2477	28
LX150.500.55.94.61.S	LX150.500.55.94.63.S	LX150.500.55.94.66.S	LX150.500.55.94.68.S	55°	4000K	2681	28
LX150.500.85.93.61.S	LX150.500.85.93.63.S	LX150.500.85.93.66.S	LX150.500.85.93.68.S	85°	3000K	2865	28
LX150.500.85.94.61.S	LX150.500.85.94.63.S	LX150.500.85.94.66.S	LX150.500.85.94.68.S	85°	4000K	2922	28
LX150.700.55.93.61.S	LX150.700.55.93.63.S	LX150.700.55.93.66.S	LX150.700.55.93.68.S	55°	3000K	3441	38
LX150.700.55.94.61.S	LX150.700.55.94.63.S	LX150.700.55.94.66.S	LX150.700.55.94.68.S	55°	4000K	3626	38
LX150.700.85.93.61.S	LX150.700.85.93.63.S	LX150.700.85.93.66.S	LX150.700.85.93.68.S	85°	3000K	3620	38
LX150.700.85.94.61.S	LX150.700.85.94.63.S	LX150.700.85.94.66.S	LX150.700.85.94.68.S	85°	4000K	3909	38



### OTHER LUMINAIRES WITHIN THE FAMILY

- Luxient 66 - Recessed
- Luxient 66 - Surface mounted
- Luxient 66 - Pendant
- Luxient 66 - Trackspot
- Luxient 90 Recessed
- Luxient 90 - Surface mounted
- Luxient 90 - Pendant
- Luxient 90 - Trackspot
- Luxient 110 - Surface mounted
- Luxient 110 - Pendant
- Luxient 125 - Recessed
- Luxient 150 - Recessed
- Luxient 150 - Pendant



Australian made like nothing ELS<sup>e</sup>.