

OVALE

IP65 Vandal resistant wall and ceiling luminaire



Product Description

A traditional wall or ceiling mounted bulkhead for exterior applications the Ovale offers IP65 protection and vandal resistant in a slim construction.

Manufactured from UV stabilised fire resistant polycarbonate in either an open or screen front face the Ovale has been designed to stand the test of time and has proven itself in the harsh Australian elements for over 25 years.

Product Details

Absolute luminous flux	410lm - 765lm
System watts	9W
Luminaire efficacy	up to 85lm/W
Colour deviation	3 SDCM
Colour rendition Index	>80
Correlated colour temperature	3000K / 4000K
Lumen maintenance	L80B10 60,000hours
Dimming method	Non dimm / DALI
Lens	UV stabilised opal polycarbonate
Body / Trim	UV stabilised flame retardant polycarbonate
Trim colour	Black / White / Silver
Country of origin	Australia

CUSTOM LUMINAIRE MODIFICATIONS

Tamper resistant allen head screws

Product Variants


TECHNICAL SPECIFICATIONS

Open face

Non Dimmable	DALI Dimmable	CCT	Lumens	Watts	Trim Colour
OVW.9.3000.61	OVW.9.3000.66	3000K	750	9	White
OVW.9.4000.61	OVW.9.4000.66	4000K	765	9	White
OVS.9.3000.61	OVS.9.3000.66	3000K	750	9	Silver
OVS.9.4000.61	OVS.9.4000.66	4000K	765	9	Silver
OVB.9.3000.61	OVB.9.3000.66	3000K	750	9	Black
OVB.9.4000.61	OVB.9.4000.66	4000K	765	9	Black

Screen

Non Dimmable	DALI Dimmable	CCT	Lumens	Watts	Trim Colour
OSW.9.3000.61	OSW.9.3000.66	3000K	410	9	White
OSW.9.4000.61	OSW.9.4000.66	4000K	420	9	White
OSS.9.3000.61	OSS.9.3000.66	3000K	410	9	Silver
OSS.9.4000.61	OSS.9.4000.66	4000K	420	9	Silver
OSB.9.3000.61	OSB.9.3000.66	3000K	410	9	Black
OSB.9.4000.61	OSB.9.4000.66	4000K	420	9	Black



OTHER LUMINAIRES WITHIN THE FAMILY

Ovale Screen



Australian made like nothing **ELSe.**