SK50 ADV

SYSTEM 50 ADVANCED | SURFACE & SUSPENDED

Customisable linear lighting solution

Product Description

Designed and made in Australia the SK 50 Advanced is a completely customisable and versatile linear lighting solution. Quality of light is key to the design of the luminaires with the option to specify a specifically engineered 'Full Spectrum' version designed to minimise potential negative effects of artificial lighting to people, pets and plants.

This amazing luminaire also features the option of a specifically engineered U diffuser to optimise vertical illuminance.

Product Details

Absolute luminous flux p/m	586lm - 1563lm
System watts p/m	13W /25W
Colour deviation	2 SDCM
Colour rendition Index	>95
Correlated colour temperature	Static White - 3000K / 4000K, Full Spectrum - 4000K
Cyanosis approval	Available with CRI 4000K
Dimming method	Non dimm / DALI / Casambi
Driver	Integral
Material	Extruded aluminium body, polycarbonate diffuser
Illumination	Direct
Optic	Opal flat diffuser / opal U diffuser
Mounting	Surface mounted / Trimless recessed / Suspended
Accessories	End caps / joiners / mitered corners / coverplate
Housing colour	Black / White / Custom
Length	Custom lengths made to order
Warranty	10 years
Colour consistency warranty	10 years
Country of origin	Australia

CUSTOM LUMINAIRE MODIFICATIONS

2700K & 3500K
IP54
Screwless endcaps

Product Variants

TECHNICAL SPECIFICATIONS - STATIC WHITE - FLAT DIFFUSER

Direct Illumination Flat Diffuser		
Delivered Lumens per 1000mm	702	1349
System Watts per meter	13	25
CRI	95+	95+
LED's divisible by	25mm	25mm

TECHNICAL SPECIFICATIONS - STATIC WHITE - U DIFFUSER

Direct Illumination U Diffuser		
Delivered Lumens per 1000mm	813	1563
System Watts per meter	13	25
CRI	95+	95+
LED's divisible by	25mm	25mm

TECHNICAL SPECIFICATIONS - FULL SPECTRUM - FLAT DIFFUSER

Direct Illumination Flat Diffuser		
Delivered Lumens per 1000mm	598	1040
System Watts per meter	13	25
CRI	95+	95+
LED's divisible by	50mm	50mm

TECHNICAL SPECIFICATIONS - FULL SPECTRUM - U DIFFUSER

Direct Illumination U Diffuser		
Delivered Lumens per 1000mm	693	1204
System Watts per meter	13	25
CRI	95+	95+
LED's divisible by	50mm	50mm

AUSTRALIAN MADE AND OWNED

Australian made like nothing ELSe.

HOW TO ORDER

SK50	.	25	.	93	.	F	.	XXXX	.	61	.	W
profile		wattage per meter down		CRI CCT		diffuser		profile length in mm		dimming type		colour finish

SK50
flat diffuser



SK50
U diffuser



OTHER LUMINAIRES WITHIN THE FAMILY

Nano 7
Nano 15
SL 30
UD 30
SL 40
UD 50
System 50
System 60
System 66
Loop 80
Valley 78

AUSTRALIAN MADE AND OWNED

Australian made like nothing ELSe.

39 Tinning Street, Brunswick, Victoria 3056 T: +61 (0)3 9222 5522 E: sales@elslighting.com.au W: elslighting.com.au