

VALLEY 78 | SURFACE & SUSPENDED

Customisable linear lighting solution



Product Description

Designed and made in Australia the VA 78 is a completely customisable and versatile linear lighting solution. The magic of this luminaire is that it presents beautifully and performs brilliantly without imposing on the overall design aesthetic.

This amazing luminaire also features the option of a specifically engineered U diffuser to optimise vertical illuminance. Available with Variable Output Technology the VA 78 ensures complete lighting control and performance for the user.

Product Details

Absolute luminous flux p/m	998lm - 3129lm
System watts p/m	9W / 12W / 17W / 21W / 26W / 30W
Colour deviation	3 SDCM
Colour rendition Index	>80 / >90
Correlated colour temperature	3000K / 4000K
Cyanosis approval	Available with 90+CRI 4000K
Lumen maintenance	L80B10 up to 72,000hours
Dimming method	Non dimm / DALI / Casambi
Driver	Integral
Material	Extruded aluminium body, polycarbonate diffuser
Optic	Opal flat diffuser
Mounting	Suspended
Accessories	End caps / joiners / suspension / coverplate
Housing colour	Black / White / Custom
Length	Custom lengths made to order divisible by 280mm
Warranty	7 years
Country of origin	Australia

CUSTOM LUMINAIRE MODIFICATIONS

2700K
 White tunable 2700K-6500K
 RGBW
 Screwless endcaps

Product Variants

TECHNICAL SPECIFICATIONS - 80+ CRI - FLAT DIFFUSER

Direct Illumination						
Delivered Lumens per 980mm	998	1376	1926	2291	2845	3129
System Watts per meter	9	12	17	21	26	30
CRI	80+	80+	80+	80+	80+	80+
LED's divisible by	140mm	140mm	140mm	140mm	140mm	140mm

TECHNICAL SPECIFICATIONS - 90+ CRI - FLAT DIFFUSER


Direct Illumination						
Delivered Lumens per 980mm	845	1165	1625	1936	2405	2645
System Watts per meter	9	12	17	21	26	30
CRI	90+	90+	90+	90+	90+	90+
LED's divisible by	140mm	140mm	140mm	140mm	140mm	140mm

TECHNICAL SPECIFICATIONS - INDIRECT ILLUMINATION

Indirect Illumination		
Delivered Lumens per 980mm	394	452
System Watts per meter	6	8
CRI	80+	90+
LED's divisible by	100mm	50mm

HOW TO ORDER

VA78	30	6	93	F	XXXX	61	W
profile	wattage per meter down	wattage per meter up	CRI CCT	lens type	profile length in mm	dimming type	colour finish



OTHER LUMINAIRES WITHIN THE FAMILY

- Nano 7
- Nano 15
- SL 30
- UD 30
- SL 40
- UD 50
- System 50
- System 60
- System 66
- Loop 80
- Valley 78



Australian made like nothing **ELS**e.