

FLEX 150 PENDANT MINI | LENS

Premium miniature surface mounted downlight with lens technology



Product Description



Presenting in a miniature size but a powerful punch, the Flex 150 Mini Pendant features up to 2500lm and optics that ensure exceptional glare control, a cornerstone of ELS's design philosophy. A large baffle provides extra visual comfort.

It is available with variable output technology to optimise performance to exact project requirements in non dimm, DALI and Casambi options.

Product Details

Absolute luminous flux	1383lm - 2535lm
System watts	14W / 20W / 28W
Luminaire efficacy	up to 96lm/W
Colour deviation	2 SDCM
Colour rendition Index	>95
Correlated colour temperature	2700K / 3000K / 3500K / 4000K
Lumen maintenance	L90B10 90,000hours
Dimming method	Non dimm / DALI / Casambi
Optic	PMMA Clear Lens
Beam angle	18° / 24° / 35° / 60°
Driver	Integral
Luminaire housing	Aluminium Powdercoated
Luminaire housing colour	Black / White / Custom
Luminaire baffle colour	Black / White / Custom
Custom body finishes	Custom powdercoat colour
Country of origin	Australia
Suspension	Clear flex 1m
Warranty	7 years

TECHNICAL SPECIFICATIONS




BLACK BAFFLE




WHITE BAFFLE

OPTIONAL ACCESSORIES



ROD KIT 500MM
ROD.KIT.500.B
ROD.KIT.500.W
An optional rod suspension kit to suit the Flex pendant range. Comes complete with 500mm rod and ceiling rose



ROD KIT 1000MM
ROD.KIT.1000.B
ROD.KIT.1000.W
An optional rod suspension kit to suit the Flex pendant range. Comes complete with 1000mm rod and ceiling rose



ROD KIT 1500MM
ROD.KIT.1500.B
ROD.KIT.1500.W
An optional rod suspension kit to suit the Flex pendant range. Comes complete with 1500mm rod and ceiling rose

OPTIONAL CLOTH FLEX



BLACK
3C.BLK
5C.BLK



GOLD
3C.GO
5C.GO



WHITE
3C.WH
5C.WH



YELLOW
3C.YL



ORANGE
3C.OR



RED
3C.RD



EMERALD
3C.EM



LIGHT BLUE
3C.LB

3 CORE OR 5 CORE

3 CORE ONLY

Product Variants

HOW TO SPECIFY

FIXED CCT

Select from the available options to configure luminaire

MODEL	OUTPUT	DISTRIBUTION	CRI	CCT	DIMMING	COLOUR FINISH
FPL150M	350 14W - 1383lm	18 18°	9 95+	27 2700K	61 NON DIM 66 DALI 68 CASAMBI	W WHITE
	500 20W - 1906lm	24 24°		3 3000K		B BLACK
	700 28W - 2535lm	35 35°		35 3500K		X CUSTOM
		60 60°		4 4000K		

Lumen outputs listed based on 4000K, 60 degree option



Australian made like nothing **ELS**e.